

the new standard  
in server technology



# Model EGA



## General

Model EGA is a modular server with many different applications. It can be used as a high-end server to control multiple IP cameras and has enough internal storage for video recordings. Model EGA can also be used as a dedicated or Virtual Host server for datacenters. The 2U chassis offers expandability – up to 7 slots for low profile RAID controller or network cards etc. Full length expansion cards can also be fitted via a horizontal riser card. The front access offers great flexibility for hot swappable hard-disk drives, fixed drives, DVD etc. Model EGA features a redundant power supply for optimum availability.

## Specific properties

The unit can be delivered in three basic configurations; with a blind front plate to mount fixed drives, with two bays on the front to accommodate up to 8 x 2.5" SFF hot swappable drives or a mix. Model EGA can be built on  $\mu$ ATX, ATX or EATX motherboards. Chassis cooling is optimized for dual Intel® XEON® CPUs. Model EGA uses energy saving fans, CPUs and power supplies and is designed to provide optimal performance from minimal energy use.

## Target group

Ecoserver model EGA is ideal for:

- High-end security environments;
- webhosting;
- dedicated server;
- virtualization server.



*ECOServer model EGA frontview*



3 Years warranty (return to factory)  
on all ECOServer models. For more  
information [www.ecoserver.eu](http://www.ecoserver.eu)

# Model EGA

## Technical properties

All systems will be configured based on the **exact needs of the application**. We provide systems without software or with Microsoft® software of your choice.

### Casing

- |                           |   |
|---------------------------|---|
| ■ <b>Type</b>             | ■ 19 inch Rackmount, 2U high,<br>inclusive Rackmountkit   |
| ■ <b>Dimensions HxWxD</b> | ■ 8,8 x 48,4 x 69,0 cm  |
| ■ <b>Weight</b>           | ■ Approximately 15 kg   |
| ■ <b>Internal storage</b> | ■ OR 9 x 3,5 inch internal HDD<br>OR 8 x 2,5 inch hotswappable SATA or<br>SAS and 3 x 3,5 inch internal SATA or SAS<br>OR Slimline DVD and 2 x 2,5 inch and<br>4 x 2,5 inch hotswappable SATA or SAS<br>and 3 x 3,5 inch internal SATA or SAS |
| ■ <b>USB ports</b>        | ■ 1 x USB 2.0 at the front  |
| ■ <b>Cooling</b>          | ■ 3 x 80 mm fan   |
| ■ <b>Colour</b>           | ■ Black   |
| ■ <b>Power supply</b>     | ■ Redundant hotswappable 500 Watt<br>power supply 100 – 240 V AC, 47 – 63 Hz<br>24 V DC or 48 V DC power supply optional  |
| ■ <b>Noise level</b>      | ■ Approximately 60 dB   |



*ECOserver EGA frontview FB*



*ECOserver EGA frontview F1*



*ECOserver EGA frontview F2*



*ECOserver EGA back*

See also [www.ecoserver.eu](http://www.ecoserver.eu)